

## Relay base - ECOR-2-BSC2-RT/4X21 - 2908214

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



ECOR-2 relay base, for industrial relays with four changeover contacts, bolt connection, for mounting on NS 35/7,5



### Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	
GTIN	4055626289144
Weight per Piece (excluding packing)	50.500 g
Custom tariff number	85366990
Country of origin	China
Note	Made to Order (non-returnable)

### Technical data

#### Dimensions

Width	29.8 mm
Height	64.9 mm
Depth	63 mm (ECOR-RHM-2)

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C

#### General

Nominal voltage $U_N$	250 V AC/DC
Nominal current $I_N$	5 A
Color	gray
Mounting position	any

# Relay base - ECOR-2-BSC2-RT/4X21 - 2908214

## Technical data

### Connection data

Connection name	Input side
Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule)
	2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross section flexible	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule)
	2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)

### Connection data 2

Connection name	Output side
Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule)
	2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross section flexible	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule)
	2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27371603
eCl@ss 11.0	27371603
eCl@ss 5.0	27371603
eCl@ss 5.1	27371603
eCl@ss 6.0	27371600
eCl@ss 7.0	27371603
eCl@ss 9.0	27371603

### ETIM

ETIM 2.0	EC001456
ETIM 3.0	EC001456
ETIM 4.0	EC001456
ETIM 6.0	EC001456
ETIM 7.0	EC001456

# Relay base - ECOR-2-BSC2-RT/4X21 - 2908214

## Classifications

### UNSPSC

UNSPSC 13.2	39122326
UNSPSC 18.0	39122335
UNSPSC 19.0	39122335
UNSPSC 20.0	39122335
UNSPSC 21.0	39122335

## Approvals

### Approvals


#### Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals


### Approval details

CSA		<a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a>	70066743
-----	---	---	----------

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 113228
---------------	---	---	---------------

cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 113228
----------------	---	---	---------------

EAC			RU C-DE.**08.B.01419
-----	---	--	----------------------

cULus Recognized			
------------------	---	--	--

## Accessories

### Accessories

## Relay base - ECOR-2-BSC2-RT/4X21 - 2908214

### Accessories

#### Loop bridge


Wire bridge - DB 50- 90 BU - 2821180

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm<sup>2</sup>, loop length: 90 mm, ferrule length: 8 mm, color: blue



Wire bridge - DB 50- 90 BK - 2820916

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm<sup>2</sup>, loop length: 90 mm, ferrule length: 8 mm, color: black



Wire bridge - DB 50- 90 GY - 2820929

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm<sup>2</sup>, loop length: 90 mm, ferrule length: 8 mm, color: gray



#### Retaining bracket

Relay retaining bracket - ECOR-RH-2L - 1051972



Relay retaining bracket, with eject function and integrated equipment marking area (8 x 25 mm), to suit relay base ECOR-2, for 29 mm high industrial relay

Relay retaining bracket - ECOR-RHM-2L - 1047026



Relay retaining bracket, wire model, suitable for ECOR-2... relay base when used with REL-IR-BL... relays

#### Necessary add-on products

## Relay base - ECOR-2-BSC2-RT/4X21 - 2908214

### Accessories

Single relay - REL-IR4-BL/L-24DC/4X21 - 2906304



Plug-in industrial relay, basic design, with power contacts, 4 changeover contacts, test key, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 24 V DC

---

Single relay - REL-IR4-BL/L-230AC/4X21 - 2906305



Plug-in industrial relay, basic design, with power contacts, 4 changeover contacts, test key, status LED, mechanical switch position indicator, input voltage: 230 V AC

---

---