


**Features**

- Trench IGBT technology
  - Low  $V_{CE(on)}$
  - Low switching losses
  - Positive  $V_{CE(on)}$  temperature coefficient
- Free wheeling diodes with fast and soft reverse recover-/y
- Industrial standard package with copper base plate

**Applications**

- Welder / Power Supply
- UPS / Inverter
- Industrial Motor Driver

**Preliminary data**




**Absolute Maximum Ratings**  $T_C = 25^\circ\text{C}$  unless otherwise noted

Item	Symbol	Conditions	Value	Units
IGBT	$V_{CES}$		1200	V
	$V_{GES}$		$\pm 20$	V
	$I_C$	@ $T_J = 175^\circ\text{C}$ , $T_C = 25^\circ\text{C}$ , Continuous	200	A
		@ $T_J = 175^\circ\text{C}$ , $T_C = 80^\circ\text{C}$ , Continuous	150	A
	$I_{CM}$	@ $T_C = 80^\circ\text{C}$ , $t_p = 1\text{ ms}$	300	A
	$T_J$	Operating Junction Temperature <sup>*(1)</sup>	-40~125	$^\circ\text{C}$
$P_D$	@ $T_J = 175^\circ\text{C}$ , $T_C = 25^\circ\text{C}$	700	W	
	@ $T_J = 175^\circ\text{C}$ , $T_C = 80^\circ\text{C}$	400	W	
Diode (FRD and INV)	$V_{RRM}$		1200	V
	$I_F$		150	A
	$I_{FRM}$	@ $t_p = 1\text{ ms}$	300	A
	$T_J$	Operating Junction Temperature <sup>*(1)</sup>	-40~125	$^\circ\text{C}$
Module	$T_{stg}$	Storage Temperature	-40~125	$^\circ\text{C}$
	$V_{iso}$	@ AC 1minute	2500	V
	$M_t$	Main Terminal Mounting torque (M5)	2.5~5	Nm
	$M_S$	Heat sink Mounting torque (M6)	3.0~5	Nm
	W	Weight	180	g

**Internal Circuit & Pin Description**

Pin Number	Pin Name	Pin Description
1	C2E1	Out
2	E2	Negative DC Link Output
3	C1	Positive DC Link Output
4	G1	Gate Input for High-side
5	E1	Emitter Input for High-side
6	G2	Gate Input for Low-side
7	E2	Emitter Input for Low-side



(Note \*1) The Maximum junction temperature of chip is 175 $^\circ\text{C}$

## Electrical Characteristics of IGBT $T_C = 25^\circ\text{C}$ unless otherwise noted

### Static Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
$BV_{CES}$	C-E Breakdown Voltage	$V_{GE} = 0\text{ V}, I_C = 1\text{ mA}$	1200	-	-	V
$I_{CES}$	C-E Cut-Off Current	$V_{CE} = V_{CES}, V_{GE} = 0\text{ V}$	-	-	1	mA
$I_{GES}$	G-E Leakage Current	$V_{GE} = V_{GES}, V_{CE} = 0\text{ V}$	-	-	-	nA
$V_{GE(th)}$	G-E Threshold Voltage	$V_{GE} = V_{CE}, I_C = 150\text{ mA}$	-	7.3	-	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C = 150\text{ A}, V_{GE} = 15\text{ V}, T_C = 25^\circ\text{C}$	-	2.2	-	V
		$I_C = 150\text{ A}, V_{GE} = 15\text{ V}, T_C = 125^\circ\text{C}$	-	2.7	-	V

### Dynamic Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
$I_{SC}$	Short Current	$V_{GE} \leq 15\text{ V}, V_{CC} = 800\text{ V}$ $V_{CE} \leq V_{CES}, T_J = 125, T_P \leq 10\mu\text{s}$	-	1000	-	A
$C_{ies}$	Input Capacitance	$V_{CE} = 30\text{ V}, V_{GE} = 0\text{ V}$ $f = 1\text{ MHz}, T_C = 25^\circ\text{C}$	-	16.3	-	nF
$C_{oes}$	Output Capacitance		-	0.7	-	nF
$C_{res}$	Reverse Transfer Capacitance		-	0.4	-	nF
$t_d(on)$	Turn-On Delay Time	$T_C = 125^\circ\text{C}, R_G = 1.8\ \Omega$ $L = 100\ \mu\text{H}, V_{DC} = 600\text{ V}$ $V_{GE} = 15\text{ V} \sim -15\text{ V}$ $I_C = 150\text{ A}$	-	237	-	ns
$t_r$	Rise Time		-	62	-	ns
$t_d(off)$	Turn-Off Delay Time		-	298	-	ns
$t_f$	Fall Time		-	185	-	ns
$E_{on}$	Turn-On Switching Loss		-	12.5	-	mJ
$E_{off}$	Turn-Off Switching Loss		-	9.6	-	mJ
$E_{ts}$	Total Switching Loss		-	22.1	-	mJ
$Q_g$	Total Gate Charge	$V_{GE} = 0\text{ V} \sim +15\text{ V}$	-	860	-	nC
$Q_{ge}$	Gate-Emitter Charge		-	200	-	nC
$Q_{gc}$	Gate-Collector Charge		-	420	-	nC

## Electrical Characteristics of Diode (FRD and INV) $T_C = 25^\circ\text{C}$ unless otherwise noted


Symbol	Parameter	Test Conditions	Min	Typ	Max	Units	
$V_F$	Diode Forward Voltage	$I_F = 150\text{ A}$ $V_{GE} = 0\text{ V}$	$T_C = 25^\circ\text{C}$	-	2.3	-	V
			$T_C = 125^\circ\text{C}$	-	2.1	-	
$t_{rr}$	Diode Reverse Recovery Time	$R_G = 1.8\ \Omega$ $L = 100\ \mu\text{H}$ $V_{DC} = 600\text{ V}$ $V_{GE} = 15\text{ V} \sim -15\text{ V}$ $I_C = 150\text{ A}$	$T_C = 25^\circ\text{C}$	-	153	-	ns
			$T_C = 125^\circ\text{C}$	-	422	-	
$I_{RRM}$	Diode Peak Reverse Recovery Current		$T_C = 25^\circ\text{C}$	-	119	-	A
			$T_C = 125^\circ\text{C}$	-	150	-	
$Q_{rr}$	Diode Reverse Recovery Charge		$T_C = 25^\circ\text{C}$	-	6.5	-	$\mu\text{C}$
			$T_C = 125^\circ\text{C}$	-	18.7	-	
$E_{rr}$	Diode Reverse Recovery Energy	$T_C = 25^\circ\text{C}$	-	1.4	-	mJ	
		$T_C = 125^\circ\text{C}$	-	6.4	-		

### Thermal Characteristics


Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
$R_{th(J-C)}$	IGBT Thermal Resistance	Junction-to-Case	-	0.21	-	$^\circ\text{C/W}$
$R_{th(J-C)D}$	Diode Thermal Resistance (FRD and INV)	Junction-to-Case	-	0.39	-	$^\circ\text{C/W}$

\* This specifications may not be considered as an assurance of characteristics and may not have same characteristics in case of using different test systems from @LSIS. We therefore strongly recommend prior consultation of our engineers.


# LUR150G1204BO/BU




**Fig 1. Typical IGBT Output Characteristics**




**Fig 2. Typical IGBT Output Characteristics**




**Fig 3. Typical IGBT Output Characteristics**



**Fig 4. Typical Diode Forward Characteristics**



**Fig 5. Typical Switching Time vs. Collector Current**



**Fig 6. Typical Switching Time vs. Collector Current**




Fig 7. Typical Switching Time vs. Gate Resistor




Fig 8. Typical Switching Time vs. Gate Resistor




Fig 9. Typical IGBT Switching Loss




Fig 10. Typical IGBT Switching Loss




Fig 11. Typical Recovery Characteristics of Diode




Fig 12. Typical Recovery Characteristics of Diode




Fig 13. Typical Diode Switching Loss




Fig 14. Typical Diode Switching Loss




Fig 15. Typical Gate Charge Characteristics




Fig 16. Case Temperature vs. Collector Current




Fig 17. Case Temperature vs. Diode Current




Fig 18. Typical IGBT Thermal Impedance





Fig 19. Typical Diode Thermal Impedance

# LUR150G1204BO/BU

## Package Dimension(Dimension in mm)



## Circuit Description

