

RL-EE-IR/L-230AC/2X21 - Single relay



1585360

<https://www.phoenixcontact.com/in/products/1585360>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Basic plug-in industrial relay with power contacts, 2 changeover contacts, test button, mechanical switching position indicator, polarity A1+, A2-, input voltage: 230 V AC

Commercial data

Item number	1585360
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	DKF943
GTIN	4067923140905
Weight per piece (including packing)	34.6 g
Weight per piece (excluding packing)	31.7 g
Country of origin	Information on the country of origin is provided with the delivery.

RL-EE-IR/L-230AC/2X21 - Single relay



1585360

<https://www.phoenixcontact.com/in/products/1585360>

Technical data

Notes

Notes on operation	Do not connect adjacent channels to SELV/ PELV and voltages dangerous to the touch.
Notes on operation	The outputs are not suitable for switching different outer conductors.
Notes on operation	Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.

Product properties

Product type	Single relay
Product family	ESSENTIAL edition
Operating mode	100% operating factor
Mechanical service life	1x 10 ⁷ cycles, approximately
B _{10d}	100000 Cycles

Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation	Basic insulation
Overvoltage category	II
Pollution degree	2

Data management status

Date of last data management	11.03.2026
------------------------------	------------

Electrical properties

Test voltage (Winding/contact)	2.5 kV _{rms} (50 Hz, 1 min.)
Test voltage (open contact)	1 kV _{rms} (50 Hz, 1 min.)
Test voltage (Changeover contact/changeover contact)	2 kV _{rms} (50 Hz, 1 min.)

Air clearances and creepage distances between the power circuits

Rated insulation voltage	250 V AC
Rated surge voltage	4 kV

Input data

Coil side

Nominal input voltage U _N	230 V AC
Input voltage range	172.5 V AC ... 299 V AC (20 °C)
Mains frequency	50/60 Hz
Drive and function	monostable
Drive (polarity)	polarized
Typical input current at U _N	7.3 mA
Input power dissipation for U _N	1.2 W
Typical response time	12 ms
Typical release time	7 ms

RL-EE-IR/L-230AC/2X21 - Single relay



1585360

<https://www.phoenixcontact.com/in/products/1585360>

Coil voltage	230 V AC
Status display	LED (yellow)

Output data

Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	250 V AC 300 V DC
Minimum switching voltage	12 V (10 mA)
Limiting continuous current	12 A
Maximum inrush current	24 A (20 ms, N/O contacts)
Min. switching current	10 mA (12 V)
Interrupting rating (ohmic load) max.	288 W (24 V DC) 130 W (48 V DC) 90 W (60 V DC) 66 W (110 V DC) 88 W (220 V DC) 90 W (300 V DC) 3000 VA (250 V AC)
Switching power min.	0.12 W
Switching capacity	4 A (24 V (DC13)) 2 A (250 V, AC15)

Environmental and real-life conditions

Ambient conditions

Degree of protection (Relay)	RT I
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m

Standards and regulations

Standards/regulations	IEC 61810-1
-----------------------	-------------

Air clearances and creepage distances between the power circuits


Standards/regulations	IEC 60664-1
-----------------------	-------------

Mounting

Mounting type	Plug-in mounting
Assembly note	in rows with zero spacing
Mounting position	any


Drawings

Diagram




Operating voltage range

Diagram




Electrical service life

Diagram



Interrupting rating AC

Diagram



Interrupting rating DC

RL-EE-IR/L-230AC/2X21 - Single relay



1585360

<https://www.phoenixcontact.com/in/products/1585360>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/1585360>



cULus Recognized

Approval ID: E172140

RL-EE-IR/L-230AC/2X21 - Single relay



1585360

<https://www.phoenixcontact.com/in/products/1585360>

Classifications

ECLASS

ECLASS-13.0	27371601
ECLASS-15.0	27371601

RL-EE-IR/L-230AC/2X21 - Single relay



1585360

<https://www.phoenixcontact.com/in/products/1585360>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in